




Informations about Geo Exte Collection

SIZES : 20X20 –20X40 –40X40
Finishes: Slate



Product group, according to the EN 14411 Norm : Bla (E < 0,5%) – UGL

Dust-pressed ceramic tiles for a floor and wall use, in internal and/or external environments

PERFORMANCES

Characteristics	Performance declared	Notes
Reaction to fire	Class A1 – A1fl	Without testing (Decision 96/603 EC as amended)
Modulus of rupture (R)	$\geq 35 \text{ N/mm}^2$	Test according to EN ISO 10545-4
Breaking strenght (S)	$> 1300 \text{ N}$ (sp. $\geq 7,5 \text{ mm}$)	Test according to EN ISO 10545-4
Skid resistance	n.p.d.	B.C.R.A. Tortus
Coefficient of friction	n.p.d.	Only for external uses in vehicular circulation areas
Bond strength	n.p.d.	Characteristic subject to the responsibility of the person charged of the tile installation (floor and wall tile installation)
Durability Frost resistance	Resistant	Test according to EN ISO 10545-12
Thermal shock resistance	Resistant	Test according to EN ISO 10545-9

GranitiFiandre S.p.a.
Via Radici Nord, 112
42014 Castellarano (RE)
Tel. 0536 /819611 – Fax 0536 850941
www.granitifiandre.com/info-ce