




Informations about Tinte Unite Collection

SIZES : 20x20 - 30X30 –30X60 –40X40 –60X60 – 120X60
Finishes: Polished – Matt – Bright – Slate



Product group, according to the EN 14411 Norm : Bla (E < 0,5%) – UGL

Dust-pressed ceramic tiles for a floor and wall use, in internal and/or external environments

PERFORMANCES

| Characteristics | Performance declared | Notes |
|--------------------------------|---|--|
| Reaction to fire | Class A1 – A1fl | Without testing (Decision 96/603 EC as amended) |
| Modulus of rupture (R) | $\geq 35 \text{ N/mm}^2$ | Test according to EN ISO 10545-4 |
| Breaking strenght (S) | $> 1300 \text{ N}$ (sp. $\geq 7,5 \text{ mm}$) | Test according to EN ISO 10545-4 |
| Skid resistance | n.p.d. | B.C.R.A. Tortus |
| Coefficient of friction | n.p.d. | Only for external uses in vehicular circulation areas |
| Bond strength | n.p.d. | Characteristic subject to the responsibility of the person charged of the tile installation (floor and wall tile installation) |
| Durability Frost resistance | Resistant | Test according to EN ISO 10545-12 |
| Thermal shock resistance | Resistant | Test according to EN ISO 10545-9 |